

HAKKO 153·154

LEAD FORMER

Lead Cutter and Former



Cutting and Forming

HAKKO 153	HAKKO 154
<p>Cutting and forming</p> <p>Max. $\phi 5$ mm</p> <p>Max. $\phi 0.8$ mm</p> <p>Min. 0.8 mm</p> <p>Min. 5.6 mm</p> <p>Max. 37 mm</p> <p>Min. 4.2 mm</p> <p>Max. 14.5 mm</p>	<p>Cutting and forming</p> <p>Max. $\phi 5$ mm</p> <p>Max. $\phi 0.5$ mm</p> <p>Min. 0.5 mm</p> <p>Min. 5 mm</p> <p>Max. 37 mm</p> <p>Min. 4.2 mm</p> <p>Max. 14.5 mm</p>
<p>Forming</p> <p>Min. 4.2 mm</p> <p>Min. 5.6 mm</p> <p>Max. 37 mm</p> <p>Max. 14.5 mm</p>	<p>Forming</p> <p>Min. 4.2 mm</p> <p>Min. 5 mm</p> <p>Max. 37 mm</p> <p>Max. 14.5 mm</p>
<p>Cutting</p> <p>Max. 50 mm</p>	<p>Cutting</p> <p>Max. 50 mm</p>



- Lead cutter and former for axial components
- Can be used for forming and cutting, forming only, or cutting only

Packing List

153, 154	Unit, Parts tray, Clamp, Handle, 2 mm Hexagon wrench, 2.5 mm Hexagon wrench, 3 mm Hexagon wrench, 4 mm Hexagon wrench, Instruction manual
-----------------	---

Specifications

Part No.	153-1	154-1
Forming size	5.6 mm pitch	5 mm pitch
Diameter of lead wire	ø0.8 mm (max.)	ø0.5 mm (max.)
Lead wire*	For annealed copper lead wire only	
Outer width of tape	85 mm (max.)	
Taping pitch	5 mm	
Dimensions	125 (W) × 130 (H) × 110 (D) mm	
Weight**	2 kg	

* These tools are not suited to work on components with lead frames (square lead).

** Including handle and clamp